

# REMOVER



## TECHNICAL DATA SHEET

### Description of the product

**REMOVER** is a special product for stripping old paints and varnishes from wood and metal surfaces. It removes old enamel paints, varnishes, emulsion and acrylic paints, 2-component polyurethane and epoxy paints. It does not drip and may be used on vertical surfaces. It **fulfills** the European legislation 276/2010/EU and does not contain methylene chloride in its formulation.

### Recommended uses

It is suitable for removing old paints and varnishes from wooden and metal surfaces.

### Technical characteristics

**Density:** 0.95±0.02 gr/ml

(EN ISO 2811.01, 20°C)

**Viscosity:** 5.5±1.5 poise

(ISO 2884.2)

**Flash point:** -5±1°C

(EAOT EN ISO 1523)

### Spreading rate

**Spreading rate:** 4.5±1.5 m<sup>2</sup>/Lt, depending on the type and oldness of paints and varnishes to be removed.

### Properties

The applications below were made on wood and metal surfaces.

#### Effectiveness:

In less than 30 minutes it removes alkyd based paints and varnishes from metal and wood surfaces.

In less than 45 minutes it removes floor varnishes from wooden surfaces.

### Application instructions

Apply a thick coat of **REMOVER** over old paints and varnishes to be stripped and let it work for 5-45 minutes. Remove softened paints and varnishes with a spatula or a scraper. Repeat the procedure if the old coatings are not properly removed. For 2-component epoxy and polyurethane paints and varnishes allow the **REMOVER** to work for longer. Flaking parts are removed. **PAINT REMOVER** is applied in a thick coat. After approximately 10 min, the surface may then be sanded and painted with the appropriate paint system, after being washed with water and let to dry thoroughly.

**Application Method:** brush or spatula.

**Thinning:** No thinning is necessary.

Tools are cleaned immediately after the application with soap and warm water.

### Packaging

Available in 0.375 Lt and 0.75 Lt cans.

### Storage

12 months, provided the cans remain closed and stored in a dry cool place away from humidity and direct sunlight.

### Health and safety

Please refer to the labeling mentioned on the can. In case more information is needed refer to the Material Safety Data Sheet.

#### Notes

- Directive 2004/42/CE is not applicable to **REMOVER**.
- The time needed for the REMOVER to work depends on the type and thickness of the coating to be removed.

*Issued: October 2020  
This issue replaces all previous ones*

