

PRERUST



TECHNICAL DATA SHEET

Description of the product

PRERUST is a water-based product for dissolving and removing rust from metal surfaces.

Recommended uses

It is used for removing rust from metal, marble and mosaic surfaces.

Technical characteristics

Density: 1.25±0.05 gr/ml

(EN ISO 2811.01, 20°C)

Viscosity: 12.5±2.5 sec

(DIN 53211/4 mm, 20°C)

PH: < 1

(ISO 976)

Application instructions

Flaking parts of rust are removed from the surface.

Metal surfaces: For severe rust apply **PRERUST** in 2-3 coats. On light rust 1 coat of **PRERUST** is enough. In that case thin with water up to 50%. Surfaces should be thoroughly washed after the application of **PRERUST**. At the end, treat the surface with an anticorrosive primer.

Marble-mosaic surfaces: **PRERUST** diluted up to 50% can be applied on marble and mosaic for removing rust and after thinning more than 50%.

Surfaces should be thoroughly washed after the application of **PRERUST**.

Application method: Brush.

Packaging

It is available in 0.9 Lt cans.

Storage

1 year, provided the cans remain closed and in normal storing conditions.

Health and safety

Please refer to the labeling mentioned on the can. In case more information is needed refer to the Material Safety Data Sheet.

Notes

- Directive 2004/42/CE is not applicable to **PRERUST**.

*Issued: December 2021
This issue replaces all others*

